Round connector

acc. to DIN EN 10241, galvanised

Application

- Connecting element for the combination of slide guides 4.0 kN and threaded pipes ½"
- For the extension and joining of threaded pipes

Your advantages

- Ideal combination of round connector and threaded pipe for a rigid attachment with greater distance from building structure
- Fast and easy extension and joining of threaded pipes
- Stable, galvanised round connector according to DIN EN 10241

Thread	Length [mm]	Outer diameter [mm]	**Part no.**	Sales unit	Pack unit
½"	34	26.6	**147091**	1	Pieces

Round connectors

for joining or connecting threaded items, galvanised

Thread	Length [mm]	Outer diameter [mm]	Max. recommended tensile load [N]	**Part no.**	Sales unit	Pack unit
M6	30	10	4,400	**113248**	100	Pieces
M8	20	11	8,100	**113254**		
	30			**113259**		
	40			**113274**		
	50			**113283**		
M10	30	13	12,800	**113175**		
	40			**113190**		
M12	30	15	18,600	**113196**		
	40			**113205**		
	55			**113220**		

Parallel couplings

for threaded rods or threaded pins, galvanised

For thread	Length [mm]	Max. recommended load [N]	**Part no.**	Sales unit	Pack unit
M8	35	1,000	**120137**	100	Pieces

Turnbuckles

with left-hand and right-hand threads and safety sight holes, galvanised

Thread	Length [mm]	Adjustment range [mm]	Max. recommended tensile load [N]	**Part no.**	Sales unit	Pack unit
M8	50	30	4,100	**125025**	100	Pieces
M10	60	40	6,500	**125007**	50	
M12	70	50	9,300	**125013**		
M16	170	120	17,700	**125019**	10	

© MÜPRO