

Pipe slides type TF-2


with two pipe clamps, DIN 3567

Application

- Attachment of pipelines preferably with insulation in heavy-duty building technology, industrial construction and plant engineering
- Preferred for insulated pipes
- For insulation thicknesses up to 140 mm

Your advantages

- Special lengths are available upon request
- Also available with polyamide sliding plate on request
- Also available in stainless steel as well as in primer coated version upon request



Features

Material	Code for material	Surface	Code for surface	Lock bolts and nuts	Code for bolts
S235JR (St37)	W37	untreated	OR	Strength class 8.8, galvanised	SG
		hot-dip galvanised	OF	Strength class 8.8, hot-dip galvanised	SF

Nominal size DN	Pipe outer Ø D [mm]	Dimensions [mm]						Loading			Weight [kg]	Design W37-OR-SG Part no.	Design W37-OF-SF Part no.	Sales unit	Pack unit
		b	s	B	H1	H2	L	F _x [kN]	F _y [kN]	F _z [kN]					
25	33.7	30	5	180	150	167	220	1	1	2	6.1	116485	116446	1	Pieces
32	42.4					171		1.4	1.4	2.6	6.2	116488	116449		
40	48.3					174		2	2	4		116491	116452		
50	60.3	40	6			180		3.2	3.2	6.4	6.8	116494	116455		
65	76.1					188		3.6	3.6	7.6	7	116497	116458		
80	88.9					195		4	4	8	7.2	116500	116461		
100	114.3	50	8			207		5.2	5.2	10.4	9.2	116476	116437		
125	139.7					220		5.5	5.5	11	9.6	116479	116440		
150	168.3					234		5.7	5.7	11.4	10.1	116482	116443		

Ordering example: T-section slide guide made from S235JR (St37) with 2 pipe clamps, pipe slide hot-dip galvanised, with hot-dip galvanised bolts and nuts, strength class 8.8, for pipe outer diameter of 76.1 mm.

Part no.: 116458, **Type:** TF-2-W37-OF-SF-76.1



Pipe guides with polyamide sliding surface as well as other versions available upon request.